

Exemption Request Form

Date of submission: January 20th, 2020

1. Name and contact details

1) Name and contact details of applicant:

Company:	Lumentum Operations LLC	Tel.: +1 408-546-4520	
Name:	Gabriela Janusz-Renault, Ph.D.	E-Mail: gabriela.janusz-renault@lumentum.com	
Function:	Sr. Manager, Compliance and	Address: 1001 Ridder Park Drive,	
	Corporate Social Responsibility	San Jose, CA 95131, USA	

2. Name and contact details of responsible person for this application (if different from above):

Company:	Lumentum Operations LLC	Tel.: +1 408-750-3877
Name:	Ramon Alvarez	E-Mail: ramon.alvarez@lumentum.com
Function:	Sr. Product Engineer	Address: 1001 Ridder Park Drive,
		San Jose, CA 95131, USA

2. Reason for application:

Please indicate where relevant:

Request for new exemption i	in:
-----------------------------	-----

Request for amendment of existing exemption in

 \boxtimes Request for extension of existing exemption in

Request for deletion of existing exemption in:

Provision of information referring to an existing specific exemption in:

🖂 Anney III	

No. of exemption in Annex III or IV where applicable: <u>32</u>

Proposed or existing wording:

"Lead oxide in seal frit used for making window assemblies for Argon and Krypton laser tubes"

Duration where applicable:

5 years

Other:

Remark: Lumentum does not manufacture Krypton lasers therefore, Argon lasers are in focus of this application.



3. Summary of the exemption request

LUMENTUM Argon laser products are used as coherent light sources in a broad range of critical applications, a majority of which are in research, bioinstrumentation and semiconductor manufacturing.

Leading manufacturers of flow cytometers, DNA sequencers, and hematology equipment incorporate LUMENTUM Argon lasers into their products for both new production and service of a large worldwide installed base. Instruments are used internationally by both government and private sector agencies for health care, drug discovery, and research applications.

In semiconductor manufacturing, LUMENTUM Argon lasers are used in inspection equipment, again for both new installations and service business.

LUMENTUM's customers have required RoHS compliance for Argon lasers since 2006, indicating possible use for other applications in scope of RoHS Directive.

The lead-oxide glass material is used in LUMENTUM's Argon laser products to provide a critical thermo-mechanically-stable and vacuum-tight seal between the optics and laser tube. The softening point of the lead-oxide based material occurs at a narrow temperature range around 420°C, and does not thermally damage the nearby fragile components being joined. Additionally the material has a coefficient of thermal expansion closely matched to the components for stress-free sealing.

The commercially available alternatives to the leaded glass sealing material (frits) are bismuth based. The bismuth based glasses have a significantly higher (540°C) melting temperatures than the lead based frits.

LUMENTUM has been searching for suitable bismuth based frit alternatives for many years and shared the test results in previous applications for RoHS exemption #32 extension. While the nominal melting temperature of bismuth based glass is 540°C, in trial builds the lead-free frit did not produce a consistent good flow of the frit material. The coverage of the frit material should be complete as in the photo on the left. As seen in the photo on the right, the lead-free material did not flow to provide a complete seal.



Figure 1: Lead based frit after processing

processing



Figure 2: Bismuth based frit after

The processing temperatures are restricted by the potential of damage to the components, primarily the optics. Because the optics utilize complex multilayer coatings (>30 layers) using higher temperatures or longer processing times is not advised by the supplier of the optics.



The coating fabrication process only allows for stabilization of the key optical properties to 500°C. Processing at temperatures above 500°C will cause failure of the coatings.

The bismuth oxide based material (frit) is not considered a viable alternative at this time. Our optics are not designed to be subjected to temperatures beyond 500°C.

4. Technical description of the exemption request / revocation request

- (A) Description of the concerned application:
 - To which EEE is the exemption request/information relevant?
 Name of applications or products:
 - a. List of relevant categories: (mark more than one where applicable)

□ 1	7
2	8 🖂
3	⊠ 9
4	🗌 10
5	🗌 11
⊠ 6	

- b. Please specify if application is in use in other categories to which the exemption request does not refer:
- c. Please specify for equipment of category 8 and 9:

The requested exemption will be applied in

 \boxtimes monitoring and control instruments in industry

in-vitro diagnostics

 \boxtimes other medical devices or other monitoring and control instruments than those in industry

2. Which of the six substances is in use in the application/product?

(Indicate more than one where applicable)

🛛 Pb	🗌 Cd	🗌 Hg	Cr-VI	PBB	PBDE
------	------	------	-------	-----	------

- 3. Function of the substance: Lowering of melting temperature in the solder glass
- 4. Content of substance in homogeneous material (%weight): >50%



- 5. Amount of substance entering the EU market annually through application for which the exemption is requested: 17 g Please supply information and calculations to support stated figure. Average annual LUMENTUM usage of PbO in the sealing glass frits in Argon lasers is about 200 g. However, only fraction of that enters EU. Based on LUMENTUM's direct shipments only 17g of PbO enters EU market annually in Argon lasers. This amount has not changed since Lumentum's previous application for RoHS exemption #32 extension in 2015.
- 6. Name of material/component: Solder glass of an argon laser tube.
- 7. Environmental Assessment:

LCA:	🗌 Yes
	🖂 No

(B) In which material and/or component is the RoHS-regulated substance used, for which you request the exemption or its revocation? What is the function of this material or component?

Lead oxide is in a solder glass frit which is used to provide a critical thermomechanically-stable and vacuum-tight seal between the optics and laser tube. Solder glass frits are made with special glass of a low softening point that is well below 500°C. Lumentum uses solder glass that has a melting point at 420°C. This glass frit joins glass of a mirror to the laser metal tube without thermally damaging complex coating layers of the mirror.

(C) What are the particular characteristics and functions of the RoHS-regulated substance that require its use in this material or component?

Lowering the glass softening point to 420°C and providing a coefficient of thermal expansion closely matched to the components for stress-free sealing.

5. Information on Possible preparation for reuse or recycling of waste from EEE and on provisions for appropriate treatment of waste

1) Please indicate if a closed loop system exist for EEE waste of application exists and provide information of its characteristics (method of collection to ensure closed loop, method of treatment, etc.)

LUMENTUM manufactures Argon lasers that are incorporated further into electrical equipment used for research, bioinstrumentation and semiconductor manufacturing. LUMENTUM's customers in EU have a legal obligation under WEEE Directive to provide appropriate treatment to the EEE waste however,



Lumentum as a component manufacturer does not have a visibility of these processes.

2) Please indicate where relevant:

- Article is collected and sent without dismantling for recycling
- Article is collected and completely refurbished for reuse

Article is collected and dismantled:

- The following parts are refurbished for use as spare parts:
- The following parts are subsequently recycled:

Article cannot be recycled and is therefore:

- Sent for energy return
- Landfilled
- 3) Please provide information concerning the amount (weight) of RoHS substance present in EEE waste accumulates per annum:

17g

In articles which are refurbished

\boxtimes In articles which are recycled	
--	--

In articles which are sent for energy return

In articles which are landfilled

6. Analysis of possible alternative substances

(A) Please provide information if possible alternative applications or alternatives for use of RoHS substances in application exist. Please elaborate analysis on a life-cycle basis, including where available information about independent research, peer-review studies development activities undertaken

No alternatives exist. See #3.

(B) Please provide information and data to establish reliability of possible substitutes of application and of RoHS materials in application

See #3.

7. Proposed actions to develop possible substitutes



(A) Please provide information if actions have been taken to develop further possible alternatives for the application or alternatives for RoHS substances in the application.

LUMENTUM has tested the initial suitability of multiple bismuth based alternatives. While the nominal melting temperatures are about 540°C, in trial builds the processing temperatures did not produce a good flow of the frit materials to seal the optics (see figure 2). In the last four years Lumentum continued test build trials with different lead-free glass frit materials but none of the lead-free alternatives produced satisfactory results.

This is because the processing temperatures of the sealing glass are restricted by the potential of damage to the components, primarily the optics. Because the optics utilize complex multilayer coatings (>30 layers) the use of higher temperatures or longer processing times is not advised by the optics supplier. The coating fabrication process only allows for stabilization of the key optical properties to 500°C and processing at temperatures above 500°C causes failure of the coatings. Therefore, the bismuth oxide glass is not considered a viable alternative to the lead based sealing glass. Multiple testing of the bismuth oxide materials even above the specified sealing times and temperatures did not provide the complete sealing needed.

In addition to the softening temperature below 500°C the seal frit is required to have the thermal expansion coefficient at 7.0 to 8.0 10⁻⁶/K to match to the components for stress-free sealing. LUMENTUM has not identified lead-free glass that meets these requirements. The table below summarizes the coefficients of thermal expansion and the sealing temperature of leaded and lead-free sealing glass and sealed components.

Table 1: Comparison of the coefficients of thermal expansion and sealing temperature of leaded and lead-free sealing glass and sealed components in the argon lasers.

Material	Coefficient of	Sealing Temperature [°C]
	Thermal Expansion [10 ⁻⁶ /K]	
G017-340	7.0	420
(leaded glass)		
G018-250	7.0	540
(lead-free glass)		
Optic	7.1	n/a
Holder	8.3	n/a



(B) Please elaborate what stages are necessary for establishment of possible substitute and respective timeframe needed for completion of such stages.

LUMENTUM has not identified lead-free glass frit material that would have a softening point below 500°C and a thermal expansion coefficient suitable for use in the Argon lasers. Lumentum has been searching for lead-free frit alternatives for over ten years, conducted trial tests on multiple bismuth based glasses but none of them provided successful results.

8. Justification according to Article 5(1)(a):

(A) Links to REACH: (substance + substitute)

- Do any of the following provisions apply to the application described under (A) and (C)?
 - Authorisation: No
 - SVHC
 - Candidate list
 - Proposal inclusion Annex XIV
 - Annex XIV

Restriction: No

Annex XVII

Registry of intentions

Registration: No. Registration is not applicable to articles. Also registration of glass is exempt (Annex V of REACH Regulation).

Lead based glass is manufactured from lead oxide and other compounds. These substances chemically react during the glass manufacturing process and form complex mixed oxide material that is not classified as SVHCs and not listed in REACH Annexes.

 Provide REACH-relevant information received through the supply chain. Name of document: _____

(B) Elimination/substitution:

1. Can the substance named under 4.(A)1 be eliminated?

☐ Yes. Consequences?
 ☐ No. Justification: Lead-free alternatives with a matching thermal expansion coefficient have higher softening point. Due to higher



processing temperatures they are not suitable for sealing of optics in Argon lasers as it would damage the optics coating.

- 2. Can the substance named under 4.(A)1 be substituted?
 - 🗌 Yes.
- Design changes:
- Other materials:
- Other substance:

🛛 No.

Justification: Bismuth based glasses are not suitable for the sealing of the optic components to the Argon laser tube due to softening point above 540°C. Temperature above 500°C damages complex coating of the laser mirrors.

Give details on the reliability of substitutes (technical data + information): See Annex for technical datasheets.

- 3. Describe environmental assessment of substance from 4.(A)1 and possible substitutes with regard to
 - 1) Environmental impacts: Negligible due to small amount of PbO used.
 - 2) Health impacts: No, due to small amount of PbO used.
 - 3) Consumer safety impacts: No
- ⇒ Do impacts of substitution outweigh benefits thereof?
 Please provide third-party verified assessment on this: _____

(C) Availability of substitutes:

- a) Describe supply sources for substitutes: None
- b) Have you encountered problems with the availability? Describe: Not applicable
- c) Do you consider the price of the substitute to be a problem for the availability?

```
🗌 Yes 🛛 🖾 No
```

d) What conditions need to be fulfilled to ensure the availability? Not applicable



- (D) Socio-economic impact of substitution:
- ⇒ What kind of economic effects do you consider related to substitution?
 Not applicable for the exemption renewal application
 - ☐ Increase in direct production costs
 - Increase in fixed costs
 - Increase in overhead
 - Possible social impacts within the EU
 - Possible social impacts external to the EU
 - Other:
- ⇒ Provide sufficient evidence (third-party verified) to support your statement: _____

9. Other relevant information

Please provide additional relevant information to further establish the necessity of your request:

Argon lasers cannot be manufactured without the use of lead oxide in seal frit of the window assembly and without Argon lasers many applications would not be possible. That includes instruments used in healthcare and research like flow cytometers, DNA sequencers, hematology equipment as well as equipment for bioinstrumentation and semiconductor manufacturing.

10. Information that should be regarded as proprietary

Please state clearly whether any of the above information should be regarded to as proprietary information. If so, please provide verifiable justification:

None of the information is proprietary.